



## KP308 8 ZONES CONVENTIONAL FIRE ALARM AND CONTROL PANEL

KP308 8 Zones conventional fire alarm panel is designed according to the latest technology in microprocessor based devices. 20 detectors (excluding button) can be connected to each zone. A total of 160 detectors can be operated. There are alarm relay output, fault relay output and siren output on the panel motherboard. It also has a 24V output. If an external device is desired to be controlled from the relay outputs, this output can be used as a supply. (see user manual for detailed information). KP308 Conventional fire alarm panel is produced with SMD Technology. It is EN 54-2/4 certified. It can work compatible with all detectors and devices that comply with EN54 standards.



### TECHNICAL SPECIFICATIONS

|                                  |   |
|----------------------------------|---|
| Operating Voltage                | :180-240 Vac                              |
| Power Consumption                | :100 W maximum                            |
| Battery Type                     | :Lead-Acid Sealed Battery                 |
| Battery Capacity                 | :2 x 12V/7Ah                              |
| Zone Capacity                    | :8  |
| Active Dedector                  |   |
| Capacity Per Zone                | :20 Pieces/Zone                           |
| Maximum Load Per Zone            | :120R                                     |
| Pasive Dedector                  |   |
| Capacity Per Zone                | :Unlimited                                |
| End of Line Resistance           | :6.8 KOhm(6.8K-20K)                       |
| Battery short-circuit Protection | :Yes                                      |
| Siren Output                     |   |
| Output Type                      | :Normally Open                            |
| Contact Strength                 | :1 A @ 30 Vdc                             |
| Fuse                             | :400 mA Automatic Reset                   |
| Maximum Voltage                  | :30V                                      |
| Alarm Relay Output               |   |
| Output Type                      | :Normally Open (NO),Normally Closed (NC)  |
| Contact Strength                 | :1 A @ 30 Vdc                             |
| Error Relay Output               |   |
| Output Type                      | :Normally Open (NO), Normally Closed (NC) |
| Contact Strength                 | :1 A @ 30 Vdc                             |
| 24V Output                       | :400mA maximum                            |

### ENVIRONMENTAL SPECIFICATIONS

|                       |                             |
|-----------------------|-----------------------------|
| Operating Temperature | :-10°C +55°C                |
| Humidity              | :%0 ≈ %95 Relative Humidity |
| IP Class              | :IP30                       |

### MECHANICAL SPECIFICATIONS

|                        |                                      |
|------------------------|--------------------------------------|
| Case Material          | :Plastic ABS + Metal Base            |
| Energy Cable Suggested | :JY(St)Y 1x2x0.8+0,8 type Fire Cable |
| Dimensions             | :26,5 x 31 x 10 cm                   |
| Weight                 | :1500 grams                          |

### GENERAL FEATURES

- Durable and aesthetic metal case and plastic front body
- 8 Zones
- Zone names can be written
- Real time clock
- Event Memory
- Turkish/English language support
- Alarm and Fault relay output
- 24V Auxiliary supply output
- EN54-2 and EN54-4 certified

